



Revolift® CFU™

Secondary Produced Water Deoiling

Enerflex's Revolift® CFU™ (Compact Flotation Unit) targets outputs as low as 20 ppm in a much smaller footprint compared to typical induced gas flotation (IGF) systems. As produced water moves continuously through multiple chambers, microbubbles are introduced to lift small suspended oil particles to the surface where they are skimmed off. The combination of sequential removal and our patented microbubble flotation (MBF®) technology allows for a highly efficient removal of sheared oils. The system is purely hydraulic with no internal moving parts, giving continuous, trouble-free separation in a single vertical tank ranging in flowrates from 10,000 to 150,000 BWPD.

How It Works

The Revolift CFU uses fluid hydraulics coupled with MBF to optimize oil-in-water separation. The multi-chambered design has no internal moving parts and requires no mechanical adjustments. Produced water enters the chambers sequentially as microbubbles are introduced. With reduced retention time, the velocities are directed centrifugally throughout each chamber to avoid short circuiting. Oil is lifted upon the bubble layer and is skimmed off by overflowing an oil weir. The water then flows into the next chamber where more microbubbles are introduced, and more oil is separated. The process drives itself hydraulically through all chambers, and water exits the system achieving targets as low as 20 ppm.

Key Benefits

Cost Saving

- Designed for easy tie in and low installation cost
- Simplified design for lower CAPEX

Better Performance

- Multi-chambered design handles variable flows, pitch and roll, and upsets without performance impact or short-circuiting problems

Flexibility

- Ability to treat difficult fluids such as heavy oils, emulsions, high viscosities, and polymer applications
- Wide turndown range allows virtually any flow rate
- Reduce your risk with a turnkey installation, or we can simply provide design and microbubble equipment
- Wide operating range handling variations in inlet water qualities
- System can be standardized for duplicated facility design across your company's locations



Standard Features

- Microbubble technology via Onyx® Pump or Gas Liquid Reactor (GLR®)
- API vertical tank design code
- Hydraulic skimming
- Piping, valves, and cabling between inlet and outlet of unit
- Instrumentation and controls for full automation with PLC based controls
- Complete process review

Materials of Construction

- Tank: FRP, internally coated
Carbon Steel or Duplex SS
- Piping: FRP, internally coated
Carbon Steel, or Duplex SS
- Instruments: 316 SS wetted parts
- Onyx Pump: Duplex SS
- GLR vessel: internally coated
Carbon Steel or Duplex 2205

Standard Options

- Water characterization services
- Chemical selection and supply
- Ancillary equipment such as transfer pumps and chemical injection
- Computational fluid dynamics modeling

This brochure is intended for general information purposes only and is not intended as a representation or warranty of any kind, or as a statement of any terms or conditions of sale. The information herein is believed to be correct, but is not warranted for correctness or completeness, or for applicability to any particular customer or situation. © 2024 Enerflex Corporation. All Rights Reserved.